

## Specification

Model No.	PD-081510-SM	PD-082010-SM	PD-IEC081510-SM	PD-IEC082010-SM
Power Rating	15A 125VAC	20A 125VAC	15A 125VAC or 10A 240VAC	20A 125VAC or 16A 240VAC
Output Receptacle Type	NEMA 5-15R x 8	NEMA 5-20R x 8	IEC320 C13 x 8	IEC320 C13 x 6 & IEC320 C19 x 2
Input Type	IEC320 C14 inlet	IEC320 C20 Inlet	IEC320 C14 Inlet	IEC320 C20 inlet
Input Phase	Single Phase	Single Phase	Single Phase	Single Phase
Mountng	1U Horizontal	1U Horizontal	1U Horizontal	1U Horizontal
Power Cord 6FT	IEC320 C13 to NEMA 5-15P, 14AWG	-	IEC320 C13 to NEMA 5-15P, 14AWG	-
Power Cord 6FT	-	IEC320 C19 to NEMA 5-20P, 12AWG	-	IEC320 C19 to NEMA 5-20P, 12AWG
Individually Switched Outlets	Yes			
Individually Metered Outlets	Yes			
Switched Relay for Outlets	Yes			
Touch Screen Display	Yes			
Overload Protection	Circuit Breaker			
Outlet Power Indicator	Indicating on TFT LCD			
Status Monitoring	Outlet current value warning can be set manually.			
IP	Dynamic IP / Static IP			
Daisy Chain Ports	USB x 2			
Ethernet Port	RJ45 x 1 with Ethernet Indicator; Gigabit Ethernet :10/100M			
Firmware Update Port	USB 2.0			
Operating Environment	-20 ~ 60°C			
Dimension	L.481.0 x W.44.2 x D.200.0 mm			
Compliance	UL/cUL 62368 & FCC		UL/cUL/IEC 62368 & FCC	