

Specification

Model No.	PD-	PD-	PD-	PD-	PD-	PD-	PD-
	081500-SM	082000-SM	G081600-SM	F081600-SM	U061300-SM	IEC082000-SM	IEC082001-SM
Power Rating	15A 125VAC	20A 125VAC	16A 250VAC	16A 250VAC	13A 250VAC	20A 125VAC or 16A 250VAC	20A 125VAC or 16A 250VAC
Output Receptacle Type	NEMA 5-15R x 8	NEMA 5-20R x 8	Schuko Sockets x 8	French Sockets x 8	UK Sockets x 6	IEC Combo x 8 C13/C15/C19/C2	IEC320 C13 x 6 IEC320 C19 x 2
Input Type	IEC320 C20 inlet						
Input Phase	Single Phase						
Finish	Black						
Front Display	Color LCD Display						
Mount Orientation	Horizontal						
Height	1U						
Network Connectivity	Yes						
Touch Screen Display	Yes						
Metered per Outlet	Yes						
Switched per Outlet	Yes						
Overload Protection	Yes						
Outlet Scheduling	Yes						
Outlet Power Indicator	Indicating on TFT LCD						
Status Monitoring	Outlet current value warning can be set manually.						
IP	Dynamic IP / Static IP						
Daisy Chain Ports	USB x 2 ; One in One out						
Ethernet Port	RJ45 x 1 with Ethernet Indicator; Gigabit Ethernet :10/100M						
Network daisy chain from	4 units						
Firmware Update Port	USB 2.0						
Operating Environment	0 ~ 50°C						
Physical Dimensions	L.481.0 x W.44.2 x D.200.0 mm						